


CHANNEL

SAFETY SYSTEMS

Ceilo



LED emergency downlight
from Channel Safety Systems



LED Downlight

The Ceilo is a recessed LED downlight; a compact fitting that utilises the latest LED technology and provides excellent value for money.


The fitting provides substantial energy and maintenance savings over the lifetime of the fitting as the unit is available either as a self-test or dali versions.

Features

- Utilises CREE X T-E
- Long life LED technology
- Polycarbonate construction
- Auto monthly and annual self test function to meet requirements of BS5266.
- Simple 'plug & go' installation
- Maintained or non maintained operation 3 hours emergency backup
- Incorporates 3.6V 2.8Ah Ni-Mh battery conditioning cycle to ensure optimal battery life
- Low environmental impact
- Beam angle 120°
- Colour temperature 6000 - 6500K
- Bi colour LED to indicate normal/fault
- Meets BS EN 60598-2-22 and other relevant standards



Image shows module, battery and lamp head



PHOTOMETRIC SPACING DATA (1 lux)

Mounting height		
2.5m	3.0	5.8
4m	3.45	6.4

SPECIFICATIONS

Light Source	CREE X T-E 6000 - 6500K (5W)
Light Output	150lm
IP Rating	IP20
Emergency Duration	≥ 3 hours
Mains Voltage	220 - 240V AC 50Hz ± 10%
Mains Current (max)	30mA
Recharge Period	24 hours
Charge Indicator	Green LED
Temperature Range	10°C - 40°C
Weight	320g
Battery	3.6V 2.8Ah Ni-Mh

PRODUCT CODE	DESCRIPTION
E/CEILO/LED/ST	Ceilo downlight self-test version
E/CEILO/LED/DALI	Ceilo downlight dali version



www.channelsafety.co.uk

Tel: 0845 884 7000

Email: sales@channelsafety.co.uk

Errors & omissions excluded. Specification is subject to change without notice.

revision 013-1