

		Nadir intensity 272cd / 1000lm		TYPICAL CONVERSIONS CFL Downlighter											
		ULOR	0.00	1 LUX MINIMUM ON CENTRE LINE ESCAPE ROUTES				0.5 LUX MINIMUM IN CORE AREA OPEN AREAS				0.2 LUX MINIMUM ON CENTRE LINE UNOBSTRUCTED ROUTES ONLY			
		DLOR	0.60	[Diagram]				[Diagram]				[Diagram]			
		LOR	0.60	[Diagram]				[Diagram]				[Diagram]			
mtg Ht (M)	ELDL	Lux level directly under	[Diagram]				[Diagram]				[Diagram]				
2.5	100	3.3	2.3	5.7	5.7	2.3	2.0	6.7	6.7	2.0	3.5	7.2	7.2	3.5	
	200	6.7	2.9	6.6	6.6	2.9	2.3	6.9	6.9	2.3	3.6	7.8	7.8	3.6	
	600	21.1	3.5	7.6	7.6	3.5	2.6	7.7	7.7	2.6	3.9	8.7	8.7	3.9	
	2000	67.0	4.1	8.2	8.2	4.1	*	*	*	*	*	*	*	*	
	4000	134.0	*	*	*	*	*	*	*	*	*	*	*	*	
4	100	1.3	2.1	6.0	6.0	2.1	2.1	8.7	8.7	2.1	4.6	10.4	10.4	4.6	
	200	2.6	3.0	8.8	8.8	3.1	3.0	9.8	9.8	3.0	5.2	11.0	11.0	5.2	
	600	7.8	4.7	10.5	10.5	4.7	3.6	11.1	11.1	3.6	5.7	12.6	12.6	5.7	
	2000	26.0	5.5	11.8	11.8	5.5	3.8	12.0	12.0	3.8	6.2	13.0	13.0	6.2	
	4000	52.0	5.7	12.6	12.6	5.7	*	*	*	*	*	*	*	*	
6	100	0.6	-	-	-	-	1.1	8.2	8.2	1.1	4.8	13.6	13.6	4.8	
	200	1.2	1.7	8.4	8.4	1.7	2.9	12.1	12.1	2.9	6.8	15.0	15.0	6.8	
	600	3.6	5.5	14.0	14.0	5.5	4.9	15.6	15.6	4.9	8.0	17.6	17.6	8.0	
	2000	12.0	7.5	17.0	17.0	7.5	5.9	17.7	17.7	5.9	9.0	18.9	18.9	9.0	
	4000	21.0	8.5	17.8	17.8	8.5	6.1	18.5	18.5	6.1	*	*	*	*	
10	100	0.2	-	-	-	-	-	-	-	-	1.6	13.0	13.0	1.6	
	200	0.4	-	-	-	-	-	-	-	-	6.5	19.6	19.6	6.522	
	600	1.2	3.9	15.0	15.0	3.9	5.2	21.6	21.6	5.2	11.5	25.6	25.6	11.5	
	2000	4.2	9.8	24.4	24.4	9.8	8.4	25.3	25.3	8.4	13.5	30.4	30.4	13.5	
	4000	8.4	12.2	27.5	27.5	12.2	9.4	26.3	26.3	9.4	15.2	33.0	33.0	15.2	

		Nadir intensity 320cd / 1000lm		TYPICAL CONVERSIONS Recessed Modular											
		ULOR	0.00	1 LUX MINIMUM ON CENTRE LINE ESCAPE ROUTES				0.5 LUX MINIMUM IN CORE AREA OPEN AREAS				0.2 LUX MINIMUM ON CENTRE LINE UNOBSTRUCTED ROUTES ONLY			
		DLOR	0.61	[Diagram]				[Diagram]				[Diagram]			
		LOR	0.61	[Diagram]				[Diagram]				[Diagram]			
mtg Ht (M)	ELDL	Lux level directly under	[Diagram]				[Diagram]				[Diagram]				
2.5	100	4.0	2.5	5.5	5.2	2.4	1.9	5.9	6.4	1.8	3.1	6.5	7.6	3.7	
	200	8.1	2.7	5.9	7.0	2.9	2.0	6.1	6.6	2.4	3.6	7.0	7.7	3.8	
	600	24.4	3.3	6.6	7.6	3.7	2.2	6.6	7.2	2.6	3.8	7.2	7.8	3.8	
	2000	81.1	3.5	6.9	7.6	3.7	*	*	*	*	*	*	*	*	
	4000	163.2	*	*	*	*	*	*	*	*	*	*	*	*	
4	100	1.6	2.9	7.2	6.4	1.9	2.5	8.6	8.8	2.2	4.5	9.8	10.4	4.6	
	200	3.2	3.6	8.6	8.8	3.2	3.0	9.1	9.9	3.0	4.9	10.2	10.6	5.1	
	600	9.6	4.6	9.8	11.0	4.7	3.4	10.4	11.0	3.8	5.3	11.4	12.1	5.6	
	2000	32.0	5.1	10.9	11.7	5.6	3.5	11.0	11.6	3.9	5.7	11.6	12.4	5.9	
	4000	64.0	5.3	11.6	12.2	5.7	*	*	*	*	*	*	*	*	
General Purpose	100	4.4	2.5	5.4	5.9	2.5	1.8	6.2	6.8	2.0	3.3	7.6	8.0	3.6	
	200	8.8	2.7	6.4	7.0	2.9	2.2	6.5	7.6	2.4	3.8	7.8	8.6	4.0	
	600	26.4	3.4	7.6	8.2	3.7	2.5	7.2	8.6	2.6	3.9	8.3	9.2	4.2	
	2000	88.0	3.8	7.8	8.6	4.0	*	*	*	*	*	*	*	*	
	4000	176	*	*	*	*	*	*	*	*	*	*	*	*	
4	100	1.7	2.2	6.8	6.80	2.0	2.3	8.6	8.9	2.3	4.4	9.8	11.6	4.8	
	200	3.4	3.4	8.6	9.2	3.4	3.0	9.5	10.5	3.2	4.9	10.8	12.4	5.8	
	600	10.2	4.5	10.1	11.8	5.0	3.5	11.2	12.6	4.1	5.7	12.6	13.9	6.4	
	2000	34.0	5.4	12.0	13.2	6.1	3.7	12.0	13.4	4.2	6.1	12.9	14.8	6.7	
	4000	64.0	5.7	12.6	14.0	6.4	*	*	*	*	*	*	*	*	

		Nadir intensity 129cd / 1000lm		TYPICAL CONVERSIONS Industrial Weatherproof											
		ULOR	0.15	1 LUX MINIMUM ON CENTRE LINE ESCAPE ROUTES				0.5 LUX MINIMUM IN CORE AREA OPEN AREAS				0.2 LUX MINIMUM ON CENTRE LINE UNOBSTRUCTED ROUTES ONLY			
		DLOR	0.57	[Diagram]				[Diagram]				[Diagram]			
		LOR	0.72	[Diagram]				[Diagram]				[Diagram]			
mtg Ht (M)	ELDL	Lux level directly under	[Diagram]				[Diagram]				[Diagram]				
2.5	100	1.9	1.6	5.8	4.6	1.5	2.0	8.0	6.5	1.6	4.5	11.6	8.7	3.4	
	200	3.8	2.9	8.2	6.4	2.3	2.8	10.7	8.0	2.2	5.8	15.0	10.6	4.6	
	600	11.4	4.9	12.5	9.4	3.6	4.3	16.0	11.0	3.2	8.6	22.0	14.8	6.0	
	2000	28.0	7.4	18.9	12.9	5.1	5.2	19.0	13.0	3.6	9.8	25.1	16.0	6.7	
	4000	47.0	8.6	22.0	14.8	6.0	*	*	*	*	*	*	*	*	
4	100	0.7	-	-	-	-	2.2	8.0	6.6	1.1	4.6	13.0	10.0	3.8	
	200	1.5	2.2	8.0	7.0	1.7	2.8	11.6	9.4	2.4	6.5	17.0	12.6	5.0	
	600	4.5	5.1	13.9	10.6	4.1	4.8	18.0	13.5	3.7	9.8	25.4	17.8	7.3	
	2000	15.2	8.5	22.0	15.8	6.2	7.7	28.0	19.5	5.5	15.0	38.0	25.0	10.3	
	4000	30.4	11.0	27.0	19.6	7.9	*	*	*	*	*	*	*	*	
6	100	0.3	-	-	-	-	-	-	-	-	3.8	13.0	10.4	3.0	
	200	0.6	-	-	-	-	1.7	11.2	9.1	1.6	6.5	17.8	14.4	5.2	
	600	2.0	4.5	14.2	11.1	3.8	4.9	19.6	15.2	3.8	10.8	28.0	21.0	8.2	
	2000	6.8	8.9	24.2	18.4	7.2	8.4	32.0	23.5	6.3	17.0	44.0	30.0	12.4	
	4000	13.6	12.1	31.6	23.7	9.2	10.8	40.0	28.0	8.0	22.0	54.0	36.0	15.0	
10	100	0.1	-	-	-	-	-	-	-	-	-	-	-	-	
	200	0.2	-	-	-	-	-	-	-	-	-	-	-	-	
	600	0.7	-	-	-	-	3.5	19.6	16.0	2.8	11.3	31.5	25.0	9.0	
	2000	2.4	8.6	20.6	20.6	7.1	9.1	36.0	28.0	7.0	19.5	52.0	38.0	15.0	
	4000	4.8	13.0	27.6	27.6	10.3	12.2	48.0	36.0	9.6	26.0	63.0	46.0	19.0	

		Nadir intensity 190cd / 1000lm		TYPICAL CONVERSIONS Recessed Modular Fitted With Flat Prismatic Diffuser											
		ULOR	0.00	1 LUX MINIMUM ON CENTRE LINE ESCAPE ROUTES				0.5 LUX MINIMUM IN CORE AREA OPEN AREAS				0.2 LUX MINIMUM ON CENTRE LINE UNOBSTRUCTED ROUTES ONLY			
		DLOR	0.47	[Diagram]				[Diagram]				[Diagram]			
		LOR	0.47	[Diagram]				[Diagram]				[Diagram]			
mtg Ht (M)	ELDL	Lux level directly under	[Diagram]				[Diagram]				[Diagram]				
2.5	100	1.8	1.3	4.4	4.4	1.3	1.6	5.6	5.6	1.6	3.4	8.6	8.6	3.4	
	200	3.6	2.3	6.2	6.2	2.3	2.2	7.0	7.0	2.2	4.3	10.6	10.6	4.3	
	600	10.8	3.6	9.2	9.2	3.6	3.2	9.5	9.5	3.2	6.1	14.8	14.8	6.1	
	2000	18	4.3	10.6	10.6	4.3	3.7	11.5	11.5	3.7	*	*	*	*	
	4000	36	5.3	13.2	13.2	5.3	*	*	*	*	*	*	*	*	
4	100	0.7	3.2	3.2	3.2	3.2	1.1	6.3	6.3	1.1	3.6	9.8	9.8	3.6	
	200	1.4	1.6	6.4	6.4	1.6	2.2	8.4	8.4	2.2	5.0	12.8	12.8	5.0	
	600	4.2	4.0	10.6	10.6	4.0	3.7	11.8	11.8	3.7	7.3	18.0	18.0	7.3	
	2000	7	5.0	12.8	12.8	5.0	4.5	14.0	14.0	4.5	8.4	20.8	20.8	8.4	
	4000	14	6.4	16.0	16.0	6.4	5.6	17.1	17.1	5.6	*	*	*	*	
6	100	0.3	-	-	-	-	-	-	-	-	2.8	10.0	10.0	2.8	
	200	0.6	-	-	-	-	1.4	9.0	9.0	1.4	5.0	14.0	14.0	5.0	
	600	1.8	3.5	11.2	11.2	3.5	3.9	13.9	13.9	3.9	8.2	20.8	20.8	8.2	
	2000	3	5.1	14.0	14.0	5.1	4.9	16.2	16.2	4.9	10.0	24.4	24.4	10.0	
	4000	6	7.1	18.4	18.4	7.1	6.4	20.3	20.3	6.4	12.2	24.0	24.0	12.2	
10	100	0.11	-	-	-	-	-	-	-	-	-	-	-	-	
	200	0.22	-	-	-	-	-	-	-	-	-	-	-	-	
	600	0.66	-	-	-	-	2.7	15.4	15.4	2.7	2.0	13.2	13.2	2.022	
	2000	1.1	2.3	13.6	13.6	2.3	4.8	19.0	19.0	4.8	8.8	24.0	24.0	8.8	
	4000	2.2	6.8	20.4	20.4	6.8	7.1	24.1	24.1	7.1	11.2	29.2	29.2	11.2	