

# CHANNEL

LIGHTING & SAFETY SYSTEMS

## i-Monitor



**DALI Wall Mount Exit Sign**  
from Channel Safety Systems



# DALI Wall Mount Exit Sign

*A stylish and compact wall mounting Single Sided LED Exit Sign that can either be surface or semi-recesses mounted.*

*The unit is a DALI Self-Test unit and is supplied with a Plexi glass screen printed legend plate offering an impressive 30m viewing distance. The legend panels are available in Arrow Up, Arrow Down, Arrow Left and Arrow Right.*

*The batteries used with this unit not only offer double the life of traditional emergency lighting batteries, but consume far less power during their operation.*



## Features

- Surface Mount (Wall)
- White Polycarbonate Body
- Extra Long Life LiFePO4 cells
- Ingress Protection Rating - IP40
- 30m Viewing Distance
- ISO Legends as Standard
- DDP (Deep Discharge Protection)
- Samsung LEDs
- Supplied With a Kit of Legends

PRODUCT CODE	DESCRIPTION
CE2S/3W/DA/AU	DALI Self-Test Wall Mount Exit Sign arrow up
CE2S/3W/DA/AD	DALI Self-Test Wall Mount Exit Sign arrow down
CE2S/3W/DA/AL	DALI Self-Test Wall Mount Exit Sign arrow left
CE2S/3W/DA/AR	DALI Self-Test Wall Mount Exit Sign arrow right



SPECIFICATIONS	
Mains Supply	230-240V AC 50/60 Hz
Power Rating - Maintained	40mA $\lambda = 0.61$
Emergency Duration	3 hours (minimum)
Recharge Period	12 Hours – Energy saving electronic charger
Battery Size & Type	9.6V 1.5Ah LiFePO4 Cells
Charge Current	0-400mA Float
Ingress Protection Rating	IP40
Class	Class II

**www.channelsafety.co.uk**

**Tel: 0845 884 7000**

**Email: sales@channelsafety.co.uk**

Errors & omissions excluded. Specification is subject to change without notice.