CHANNEL
Smarter Safety®

EXITOR

LED emergency exit signage
from Channel Safety Systems

AC 230-240V

LED

IP20

Emergency Exit Sign

The Exitor utilises LED technology for low cost, high output, emergency illumination.

Features

- Maintained or Non-maintained 3 hour emergency back-up
- Down light panel LEDs to illuminate exit door.
- Low environmental impact
- Minimal maintenance
- Meets BS EN 60598-2-22 and other relevant standards
- Lightweight & easy to install, hinged cover
- Low environmental impact
- Minimal maintenance
- Supplied with full legend set





Note: Image not to scale and for pictorial reference only

SPECIFICATIONS	
Light Source	SMT LED 3W
Colour Temperature	5500K
IP Rating	IP20
Emergency Duration	3 hours (minimum)
Mains Voltage	230V 50Hz ± 10%
Mains Current	CHARGING 55-90MA - 35mA quiescent (3W)
Recharge Period	Less than 24 hour
Charge Indicator	Integral green LED
Changeover Voltage	As per the requirements of BS EN 60598-2-22
Temperature Range	5°C to 40°C
Weight	690gm
Battery	3.6V 1200mAh Nickel Cadmium
Material & Finish	Polycarbonate construction, white/opal finish

PRODUCT CODE	DESCRIPTION
E/EX/M3	EXITOR LED exit sign c/w full legend set

www.channelsafety.co.uk
Tel: 0845 884 7000
Email: sales@channelsafety.co.uk

Errors & ommissions excluded. Specification is subject to change without notice.